


FML-R22-MCT

Customer Name: \_\_\_\_\_

Project Name: \_\_\_\_\_

Note: \_\_\_\_\_ | Type: \_\_\_\_\_



22" x 1"

Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

## Features

- Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Wet Location Performance
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Die-cast Aluminum. Powder-Coated
- 5-Year Warranty
- 1" Deep

## Technical Specifications

### Electrical:

- Voltage: 120V AC
- Power Factor: >0.90
- Wattage: 45W
- Efficacy: 60 LPW

### Mechanical:

- White Finish
- Die-cast Aluminum. Powder-Coated
- Maximum Ambient Temperature: 104°F
- Rated life: 50,000 hrs

### Lighting:

- Lens: White translucent acrylic lens
- LED: Edge Lit LED Technology
- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- Total Lumens: 2700LM
- Color Temperatures: 3000K/ 4000K/ 5000K
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Color Rendering Index: CRI ≥ 90

### Applications:



- Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

### Other Models:


• 11W | 660LM | FML-R6-MCT • 14W | 840LM | FML-R8-MCT • 17W | 1020LM | FML-R10-MCT • 26W | 1560LM | FML-R14-MCT • 30W | 2100LM | FML-R18-MCT



## Photometrics: FML-R22-MCT



BUG Rating: B1-U2-G1



Simulation Based on 4000K Area 50' x 50' Mounting Height: 9'

## Other Views:



Side View



Front View



Back View

## Performance Table: FML-R22-MCT

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
FML-R22-MCT	45W	120V	2700LM	3000K/ 4000K/ 5000K	B1-U2-G1	60

## Sample Ordering

-  -

## Accessory:

Blank = No Option For Accessories  
 FML-ULK-MCT = UPLIGHT MODULE FOR 18in AND LARGER FML SERIES, 15W, 30K/40K/50K 14" DIAMETER, 900 LUMENS  
 FML-RK-712 = 7in/12in ROD KIT FOR FML SEMI-FLUSH INSTALLATIONS BOTH LENGTHS PROVIDED IN THE KIT TO CHOOSE  
 FML-SK6 = 6FT ADJUSTABLE SUSPENSION KIT FOR 18IN AND LARGER FML SERIES

## Example:

1. FML-R22-MCT (FOR FML R22 MCT FIXTURE 120-277V)
2. FML-R22-MCT (FOR FML R18 MCT FIXTURE 120-277V)  
 FML-SK6 (6FT ADJUSTABLE SUSPENSION KIT FOR 18IN AND LARGER FML SERIES )

## ACCESSORIES:



**FML-ULK-MCT**  
 UPLIGHT MODULE FOR 18in AND LARGER FML SERIES  
 14" DIAMETER, 900 LUMENS



**FML-SK6**  
 6' ADJUSTABLE SUSPENSION CABLE WITH CANOPY AND POWER CORD



**FML-RK-712**  
 7in/12in ROD KIT FOR FML SEMI-FLUSH INSTALLATIONS  
 BOTH LENGTHS PROVIDED IN THE KIT TO CHOOSE

